KINGSAT

Hangzhou Saikeling Electric Technology Co., Ltd

DATASHEET

Camera Lens Washer Tank

Pressurised washer for wiper PTZ and wiper bullet cameras — clears salt and soot without sending a crew member up the mast.

CATEGORY
Accessory

MODELS
—

SIZE CLASS
5 L · 27 PSI

SPECIFICATION

Parameter	Value
Intended for	Wiper PTZ and wiper bullet cameras
Reservoir	5 L, built into the housing
Pump	Vacuum motor pump
Working pressure	27 PSI
Flow rate	> 1.9 L/min
Hose length	5 m
Hose	Polyethylene, automotive grade, 4 mm inside diameter
Outlet	1 × Ø6×4 (1/4 in) or M20
Body material	SUS 304 / 304 / 316L stainless steel (optional)
Temperature range	0 to +60 °C
Power supply	DC 12 V
Power consumption	10 W max

Transcribed from the Saikeling 2026 product manual. This page has no separate data table in the catalogue; the values above are the published specification list.

AT A GLANCE

— 5 L reservoir with built-in vacuum pump
— 27 PSI working pressure, more than 1.9 L/min flow
— 5 m automotive-grade PE hose, 4 mm inside diameter
— 304 or 316L stainless steel body
— DC 12 V, 10 W maximum